

Diesel Generator Set Model DFJD 60 Hz

1000 kW, 1250 kVA Standby
900 kW, 1125 kVA Prime



Description

The Cummins Power Generation DF-series commercial generator set is a fully integrated power generation system providing optimum performance, reliability, and versatility for stationary standby or prime power applications.

A primary feature of the DF GenSet is strong motor-starting capability and fast recovery from transient load changes. The torque-matched system includes a heavy-duty Cummins 4-cycle diesel engine, an AC alternator with high motor-starting kVA capacity, and an electronic voltage regulator with three-phase sensing for precise regulation under steady-state or transient loads. The DF GenSet accepts 100% of the nameplate standby rating in one step, in compliance with NFPA110 requirements.

The standard PowerCommand[®] digital electronic control is an integrated system that combines engine and alternator controls for high reliability and optimum GenSet performance.

Optional coolant heaters improve starting in extreme operating conditions. A wide range of options, accessories, and services are available, allowing configuration to your specific power generation needs.

Every production unit is factory tested at rated load and power factor. This testing includes demonstration of rated power and single-step rated load pickup. Cummins Power Generation manufacturing facilities are registered to ISO9001 quality standards emphasizing our commitment to high quality in the design, manufacture, and support of our products. The generator set is CSA certified, and the PowerCommand control is UL508 listed.

All Cummins Power Generation systems are backed by a comprehensive warranty program and supported by a worldwide network of 170 distributors and service branches to assist you with warranty, service, parts, and planned maintenance support.

Features

- **Cummins Heavy-Duty Engine** - Rugged 4-cycle industrial diesel delivers reliable power, low emissions, and fast response to load changes.
- **Permanent Magnet Generator (PMG)** - Offers enhanced motor starting and fault clearing short circuit capability.
- **Alternator** - Several alternator sizes offer selectable motor starting capability with low reactance 2/3 pitch windings; low waveform distortion with non-linear loads, fault clearing short-circuit capability, and class H insulation.
- **Control System** - The PowerCommand electronic control is standard equipment and provides total genset system integration, including automatic remote starting/stopping, precise frequency and voltage regulation, alarm and status message display, AmpSentry[™] protection, output metering, auto-shutdown at fault detection, and NFPA 110 compliance.
- **Cooling System** - Provides reliable running at rated power in ambient temperatures through 50°C.
- **Structural Steel Skid Base** - Robust skid base supports the engine, alternator, and radiator.
- **E-Coat Finish** - Dual electro-deposition paint system provides high resistance to scratches, corrosion, or fading.
- **Certifications** - Generator sets are designed, manufactured, tested, and certified to relevant UL, NFPA, ISO, IEC, and CSA standards.
- **Warranty and Service** - Backed by a comprehensive warranty and world wide distributor network.

Generator Set

The general specifications provide representative configuration details. Consult the outline drawing for installation design.

Specifications – General

See outline drawing 500-2957 for installation design specifications.

Unit Width, in (mm)	74.6 (1894)
Unit Height, in (mm)	98.7 (2507)
Unit Length, in (mm)	190.0 (4826)
Unit Dry Weight, lb (kg)	19500 (8845)
Unit Wet Weight, lb (kg)	20570 (9331)
Rated Speed, rpm	1800
Voltage Regulation, No Load to Full Load	±0.5%
Random Voltage Variation	±0.5%
Frequency Regulation	Isochronous
Random Frequency Variation	±0.25%
Radio Frequency Interference	IEC 801.2, Level 4 Electrostatic Discharge IEC 801.3, Level 3 Radiated Susceptibility IEC 801.4, Level 4 Electrical Fast Transients IEC 801.5, Level 5 Voltage Surge Immunity MIL STD 461C, Part 9 Radiated Emissions (EMI)

Cooling	Standby	Prime
Fan Load, HP (kW)	58.0 (43.3)	58.0 (43.3)
Coolant Capacity with radiator, US Gal (L)	88.9 (336.5)	88.9 (336.5)
Coolant Flow Rate, Gal/min (L/min)	390.0 (1476.2)	390.0 (1476.2)
Heat Rejection To Coolant, Btu/min (MJ/min)	38740.0 (41.1)	35100.0 (37.2)
Heat Radiated To Room, Btu/min (MJ/min)	12180.0 (12.9)	11030.0 (11.7)
Maximum Coolant Friction Head, psi (kPa)	10.0 (68.9)	10.0 (68.9)
Maximum Coolant Static Head, ft (m)	60.0 (18.3)	60.0 (18.3)

Air	Standby	Prime
Combustion Air, scfm (m ³ /min)	3040.0 (86.0)	2880.0 (81.5)
Alternator Cooling Air, scfm (m ³ /min)	6720.0 (190.2)	6720.0 (190.2)
Radiator Cooling Air, scfm (m ³ /min)	53750.0 (1521.1)	53750.0 (1521.1)
Max. Static Restriction, in H ₂ O (Pa)	0.5 (124.5)	0.5 (124.5)

Rating Definitions

Standby Rating based on: Applicable for supplying emergency power for the duration of normal power interruption. No sustained overload capability is available for this rating. (Equivalent to Fuel Stop Power in accordance with ISO3046, AS2789, DIN6271 and BS5514). Nominally rated.

Prime (Unlimited Running Time) Rating based on: Applicable for supplying power in lieu of commercially purchased power. Prime power is the maximum power available at a variable load for an unlimited number of hours. A 10% overload capability is available for limited time. (Equivalent to Prime Power in accordance with ISO8528 and Overload Power in accordance with ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

Base Load (Continuous) Rating based on: Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating. (Equivalent to Continuous Power in accordance with ISO8528, ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

Site Derating Factors

Rated power available up to 5300 ft (1617 m) at ambient temperatures up to 104°F (40°C). Above 5300 ft (1617 m), derate at 4% per 1000 ft (305 m) and 1% per 10°F (2% per 11°C) above 104°F (40°C).

Engine

Cummins heavy duty diesel engines use advanced combustion technology for reliable and stable power, low emissions, and fast response to sudden load changes.

Electronic governing provides precise speed regulation, especially useful for applications requiring constant (isochronous) frequency regulation such as Uninterruptible Power Supply (UPS) systems, non-linear loads, or sensitive electronic loads. Optional coolant heaters are recommended for all emergency standby installations or for any application requiring fast load acceptance after start-up.

Specifications – Engine

Base Engine	Cummins Model KTA38-G4, Turbocharged and Aftercooled, diesel-fueled
Displacement in³ (L)	2300.0 (37.7)
Overspeed Limit, rpm	2100 ±50
Regenerative Power, kW	164.00
Cylinder Block Configuration	Cast Iron with replaceable wet cylinder liners, 60° V 12 cylinder
Cranking Current	890 amps at ambient temperature of 32°F (0°C)
Battery Charging Alternator	45 amps
Starting Voltage	24-volt, negative ground
Lube Oil Filter Types	Four spin-on, full flow
Standard Cooling System	122°F (50°C) ambient radiator

Power Output	Standby	Prime							
Gross Engine Power Output, bhp (kWm)	1490.0 (1111.5)	1350.0 (1007.1)							
BMEP at Rated Load, psi (kPa)	281.0 (1937.4)	254.0 (1751.3)							
Bore, in. (mm)	6.25 (158.8)	6.25 (158.8)							
Stroke, in. (mm)	6.25 (158.8)	6.25 (158.8)							
Piston Speed, ft/min (m/s)	1875.0 (9.5)	1875.0 (9.5)							
Compression Ratio	13.9:1	13.9:1							
Lube Oil Capacity, qt. (L)	136.0 (128.7)	136.0 (128.7)							
Fuel Flow									
Maximum Fuel Flow w/c180, US Gal/hr (L/hr)	134.0 (507.2)	134.0 (507.2)							
Maximum Fuel Flow w/c174, US Gal/hr (L/hr)	260.0 (984.1)	260.0 (984.1)							
Maximum Inlet Restriction, in. Hg (mm Hg)	4.0 (101.6)	4.0 (101.6)							
Maximum Return Restriction, in. Hg (mm Hg)	6.5 (165.1)	6.5 (165.1)							
Air Cleaner									
Maximum Air Cleaner Restriction, in. H ₂ O (kPa)	25.0 (6.2)	25.0 (6.2)							
Exhaust									
Exhaust Flow at Rated Load, cfm (m ³ /min)	8405.0 (237.9)	7715.0 (218.3)							
Exhaust Temperature, °F (°C)	975.0 (523.9)	930.0 (498.9)							
Max Back Pressure, in. H ₂ O (kPa)	41.0 (10.2)	41.0 (10.2)							
Fuel System	Direct injection, number 2 diesel fuel; fuel filter; automatic electric fuel shutoff								
Fuel Consumption	Standby	Prime							
60 Hz Ratings, kW (kVA)	1000 (1250)	900 (1125)							
	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full	
	US Gal/hr	24.7	39.8	54.5	70.1	23.4	36.6	50.1	63.3
	L/hr	93	151	206	265	89	139	190	240

Alternator

Several alternators are available for application flexibility based on the required motor-starting kVA and other requirements. Larger alternator sizes have lower temperature rise for longer life of the alternator insulation system. In addition, larger alternator sizes can provide a cost-effective use of engine power in across-the-line motor-starting applications and can be used to minimize voltage waveform distortion caused by non-linear loads.

Single-bearing alternators couple directly to the engine flywheel with flexible discs for drivetrain reliability and durability. No gear reducers or speed changers are used. Two-thirds pitch windings eliminate third-order harmonic content of the AC voltage waveform and provide the standardization desired for paralleling of generator sets. The standard excitation system is a PMG excited system.

Alternator Application Notes

Separately Excited Permanent Magnet Generator (PMG) System - This standard system uses an integral PMG to supply power to the voltage regulator. A PMG system generally has better motor-starting performance, lower voltage dip upon load application, and better immunity from problems with harmonics in the main alternator output induced by non-linear loads. This system provides improved performance over self-excited regulators in applications that have large transient loads, sensitive electronic loads (especially UPS applications), harmonic content, or that require sustained short-circuit current (sustained 3-phase short circuit current at approximately 3 times rated for 10 seconds).

Alternator Sizes - On any given model, various alternator sizes are available to meet individual application needs. Alternator sizes are differentiated by maximum winding temperature rise, at the generator set standby or prime rating, when operated in a 40°C ambient environment. Available temperature rises range from 80°C to 150°C. Not all temperature rise selections are available on all models. Lower temperature rise is accomplished using larger alternators at lower current density. Lower temperature rise alternators have higher motor-starting kVA, lower voltage dip upon load application, and they are generally recommended to limit voltage distortion and heating due to harmonics induced by non-linear loads.

Alternator Space Heater - is recommended to inhibit condensation.

Available Output Voltages

Three Phase Reconnectable

- [] 120/208
- [] 127/220
- [] 139/240
- [] 220/380
- [] 240/416
- [] 254/440
- [] 277/480

Three Phase Non-Reconnectable

- [] 277/480
- [] 347/600

Specifications – Alternator

Design	Brushless, 4 pole, drip proof revolving field
Stator	2/3 pitch
Rotor	Direct coupled by flexible disc
Insulation System	Class H (low voltage) or Class F (medium voltage) per NEMA MG 1-1.65 and BS2757.
Standard Temperature Rise	125°C @ Standby, 105°C @ Prime
Exciter Type	Permanent Magnet Generator (PMG)
Phase Rotation	A (U), B (V), C (W)
Alternator Cooling	Direct drive centrifugal blower
AC Waveform Total Harmonic Distortion	<5% total no load to full linear load <3% for any single harmonic
Telephone Influence Factor (TIF)	<50 per NEMA MG1-22.43
Telephone Harmonic Factor (THF)	<3

Three Phase Table¹		80° C	80° C	105° C	105° C	125° C	125° C	125° C	125° C	125° C			
Feature Code		B284	B302	B283	B301	B252	B282	B288	B276	B300			
Alternator Data Sheet Number		314	313	313	312	312	313	312	311	311			
Voltage Ranges		220/380 Thru 277/480	347/600	220/380 Thru 277/480	347/600	120/208 Thru 139/240 240/416 Thru 277/480	220/380 Thru 277/480	240/416 Thru 277/480	277/480	347/600			
Surge kW		1021	1023	1012	1024	1019	1012	1019	1018	1018			
Motor Starting kVA (at 90% sustained voltage)	PMG	5521	4602	4602	4234	4234	4602	4234	3866	3866			
Full Load Current - Amps at Standby Rating		<u>120/208</u> 3469	<u>127/220</u> 3280	<u>139/240</u> 3006	<u>220/380</u> 1899	<u>240/416</u> 1734	<u>254/440</u> 1640	<u>277/480</u> 1503	<u>347/600</u> 1203				

Notes:

1. Single Phase Capability: Single phase power can be taken from a three phase generator set at up to 40% of the generator set nameplate kW rating at unity power factor.

Control System



Optional Features Shown

<p>PowerCommand® Control with AmpSentry™ Protection</p> <ul style="list-style-type: none"> • AmpSentry Protection guards the electrical integrity of the alternator and power system from the effects of overcurrent, over/under voltage, under frequency and overload conditions. • Control components are designed to withstand the vibration levels typical in generator sets. • Integrated automatic voltage regulator and engine speed governor 		
<p>Standard Control Description</p> <ul style="list-style-type: none"> • Analog % of current meter (amps) • Analog % of load meter (kW) • Analog AC frequency meter • Analog AC voltage meter • Cycle cranking control • Digital display panel • Emergency stop switch • Idle mode control • Menu switch • Panel backlighting • Remote starting, 24 V, 2 wire • Reset switch • Run-Off-Auto switch • Sealed front panel, gasketed door • Self diagnostics • Separate customer interconnection box • Voltmeter/Ammeter phase selector switch 		
<p>Standard Protection Functions</p>		
<p>Warnings</p> <ul style="list-style-type: none"> • High coolant temperature • High DC voltage • Low coolant temperature • Low DC voltage • Low fuel-day tank • Low oil pressure • Oil pressure sender fault • Overcurrent • Overload load shed contacts • Temperature sender fault • Up to four customer fault inputs • Weak battery 	<p>Shutdowns</p> <ul style="list-style-type: none"> • Emergency stop • Fail to crank • High AC voltage • High coolant temperature • Low AC voltage • Low coolant level (option for alarm only) • Low oil pressure • Magnetic pickup failure • Overcrank • Overcurrent • Overspeed • Short circuit • Underfrequency 	<p>Standard Performance Data</p> <p>AC Alternator</p> <ul style="list-style-type: none"> • Current by phase • Kilowatts • Kilowatt hours • Power factor • Voltage line to line • Voltage line to neutral <p>Engine Data</p> <ul style="list-style-type: none"> • Battery voltage • Coolant temperature • Engine running hours • Engine starts counter • Oil pressure • Oil temperature • RPM

Generator Set Options

Engine

- 75 A battery charging alternator
- Dual 208/240/480 V, coolant heaters 10,000 & 12, 840 total W packages available
- Dual 120 V, 300 W lube oil heaters
- Dual 208/240 V, 300 W lube oil heaters
- Dual 480 V, 300 W lube oil heaters
- Bypass oil filter
- Fuel water separator
- Heavy-duty air cleaner with safety element

Cooling System

- Heat exchanger cooling
- Remote radiator cooling

Alternator

- 12 Lead alternator
- 80°C rise alternator
- 105°C rise alternator
- 120/240 V, 300 W anti-condensation heater

Control Panel

- 120/240 V, 100 W control anti-condensation space heater
- Exhaust pyrometer
- Fuel-pressure gauge (engine mounted)
- Remote fault signal dry contact relay package
- Run relay package

Exhaust System

- Critical-grade exhaust silencer
- Industrial grade exhaust silencer
- Residential grade exhaust silencer

Generator Set

- AC entrance box
- Batteries
- Battery charger, equalizer, float-type
- Export box packaging
- Ground fault alarm
- Main line circuit breaker
- Paralleling accessories
- Remote annunciator panel
- Spring isolators
- 2 year standby warranty
- 2 year prime power warranty
- 5 year basic power warranty
- 5 year comprehensive power warranty
- 10 year major components warranty

Available Products and Services

A wide range of products and services is available to match your power generation system requirements. Cummins Power Generation products and services include:

- Diesel and Spark-Ignited Generator Sets
- Transfer Switches
- Bypass Switches
- Parallel Load Transfer Equipment
- Digital Paralleling Switchgear
- PowerCommand Network and Software
- Distributor Application Support
- Planned Maintenance Agreements

Warranty

All components and subsystems are covered by an express limited one-year warranty. Other optional and extended factory warranties and local distributor maintenance agreements are available. Contact your distributor/dealer for more information.

Certifications



ISO9001 - This generator set was designed and manufactured in facilities certified to ISO9001.



CSA - This generator set is CSA certified to product class 4215-01.



PTS - The Prototype Test Support (PTS) program verifies the performance integrity of the generator set design. Products bearing the PTS symbol have been subjected to demanding tests in accordance to NFPA 110 to verify the design integrity and performance under both normal and abnormal operating conditions including short circuit, endurance, temperature rise, torsional vibration, and transient response, including full load pickup.



UL - The PowerCommand control is Listed to UL508 - Category NITW7 for U.S. and Canadian usage.

See your distributor for more information



Cummins Power Generation
1400 73rd Avenue N.E.
Minneapolis, MN 55432
763.574.5000
Fax: 763.574.5298
www.cumminspowergeneration.com

Cummins and PowerCommand are registered trademarks of Cummins Inc.
Detector and AmpSentry are trademarks of Cummins Inc.

Important: Backfeed to a utility system can cause electrocution and/or property damage. Do not connect generator sets to any building electrical system except through an approved device or after building main switch is open.